



TECHNICALL

The RUKRA elevator cables suitable for connecting:

- Elevator Phone
- Analog elevator camera
- IP camera elevator
- Code keypad
- Pass Reader
- Multimedia Screen
- Intercom connection

The cables are all weather, UV and oil resistant

• Article numbers:



RK-7610



RK-7611

RUKRA ELEVATORCABLE CATSE

The RUKRA Elevator cables are specially designed for use in elevators with a maximum spacing of 100 meters. The cables are suitable for indoor and outdoor installation, in dry and wet locations.

RK-7610 RUKRA ELEVATOR CABLE CAT5E with strain relief Structure:

ESSENTIAL LINE FD P CAT5e 4X2XAWG26

- Core identification: blue, white, orange and white, green and white, brown and white.
- Kevlar braid 16 wires (tensile 7kg per thread)
- Nitrile smooth outer shell wall thickness approx 1.8mm
- Outside diameter approximately 10.5mm

RK-7611 RUKRA ELEVATOR CABLE PVC C (2x0,34) + 2 x 2x0,34 HYBRID Structure:

- 2 pairs 2x0,34mmÇ wrapped with PP film
- 1 pair 2x0,34mmÇ wrapped with ALU foil, braid screen tinned copper foil tape about fleece
- The three data pairs are beaten together with three gripolene rope fillers (total traction 1000N)
- Soft Nitrile outer shell wall thickness approx 1.8mm
- Outside diameter approx 11mm